

ALGONQUIN COMMONS THEATRE TECHNICAL SPECIFICATIONS

Updated: June 2025

700-seat theatre (177 Floor Level / 303 Main Level / 220 Balcony Level)
When the floor seats are removed, the venue capacity increases to 835

VENUE

- 78'w x 37'd stage with 48'w x 20'h proscenium arch opening
- (2) 53' flat loading docks with tour bus shore power
- (2) ten person choir line dressing rooms with bathrooms and showers
- (2) single person dressing rooms with bathroom and shower
- 30'w x 30'd Green Room with kitchenette
- (1) visiting technical director/promoter office
- (1) Laundry Room
- Scan card entry for back of house
- Wheelchair accessible
- Professional non-union crew

AUDIO

- Removable Meyer Sound system installed comprised of Meyer JM-1P's, UPQ-1P's and 1100-LFC's
- DiGiCo SD9 audio consoles at FOH and on stage
- Digital and analog audio snake installed
- (14) Meyer MJF-212A stage monitors
- (1) Meyer ULTRA-X42 top fill monitor installed over stage
- Full in house mic package including 4 wireless kits, and 10 piece DPA Rock Kit
- "Off the floor" recording possible in-house
- Assistive listening system installed

LIGHTING

- GrandMA 3 Lite Lighting Console
- 182 dimmer channels installed on catwalks, boom boxes, side light positions and balcony rail
- 22 patch point Pathport sACN DMX distribution system installed
- ETC Source Four Lekos Stage Wash; Fronts, tips, Backs and gel'd colours (House plot)
- 12 x Mac Era 600 Profile & 12 x Mac Aura LED Fresnel wash light on 2 x 40' Truss installed on chain motors (House plot)
- 5 x Chroma Q Colorforce Cyc wash (house plot) plus 2 available at an additional cost
- 3 x Lycian M2 Followspot (additional cost)
- 16 x Martin Rush MH3 (additional cost)
- 8 x Martin Atomic Strobe (additional cost)
- 1 x Ultratec Radiance Haze System (additional cost)
- Additional stock fixtures including ETC Source Four Fresnel's, ETC 15°-30° Leko Zoom and 5°, 14°, 19°, 26°, & 36° Barrels for ETC Source Four Lekos

VIDEO

- 12000 Lumens installed Barco projector
- Retractable 27'w x 15.5'h white film screen
- Versatile scaling and switching system by Crestron
- Compatible with HDMI, VGA, and DVI output devices
- Confidence Monitor and Perfect Q system available
- Professional in-house HD live streaming and video recording services available

TOUR POWER

- (2) 200A, 3phase, 5wire for lighting on SL
- (1) 100A, 3phase, 5wire for audio on SL (Isolated Transformer)
- (1) 100A, 3phase, 5wire in loading dock for mobiles
- (2) 200A, 3phase, 5wire on East side of building
- (1) 100A, 3phase, 5wire in Central Park
- (2) shore power for tour bus

SOFT GOODS

- Main drape traveler
- Mid stage traveler
- Upstage traveler
- 40'w x 26'h Cyclorama
- (2) sets of fixed legs
- (4) retractable side tabs per side
- Motorized backdrop line set

STAGE ACCESSORIES

- Installed Clear-Com system to all dressing rooms, BOH, FOH, and various tie positions plus wireless Clear-Com packs
- (6) 8'x4' risers. Adjustable 12"-18". Rolling capable.
- Black podium with microphones and littlite
- 40'w x 26'h Cyclorama
- Custom cut harlequin black cascade dance floor cover available (additional cost)
- 12 metric ton rigging rating for OWJ's over stage (rigging plot required for review, 2 ton per point max)
- Steinway & Sons Model D: 9' Concert Grand Piano
- Wireless Dsan Limitimer System

**Additional subrental equipment may be
available as requested/required**